

Fig. 1





Fig. 2



Fibre Channel Arbitrated Loop Hub

Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7



8/52




Fig. 8



9/52





Fig 9a




10/52




Connection established.
Open sourced

Fig 9b




11/52




Arbf0 replaced with Arbff. Data Transferred.
Close sourced.

Fig 9c



Arbff detected on port rx_data.
 Disconnect. Source idles

Fig 9d




Arbs forwarded. Open sourced.

Fig 10a



14/52



Open detected at port receiver.
Port receiver holds open.
Provides ALPA to router and asserts `opn_connect_req`.

Fig 10b



15/52






Fig 10c



Arbfff detected on port rx_data. Disconnect. Source idles.

Fig 10d




Arbs forwarded.
Open Sourced.

Fig 11a



18/52




Arb 13 forwarded.
Data Transferred.
Close sourced.

Fig 11b



19/52




Close forwarded by node 12.
Arb 13 received by node 13.
Open sourced by node 13.

Fig 11c




20/52



Close source by node 13.
Forwarded by node 12.
Arb ff Detected on port rx_data.
Disconnect.
Source idles.

Fig 11d



21/52





Fig 12a




Open forwarded to Port 2.	Open received from Port 1.
Data transferred.	Data received.
Close sourced.	Close forwarded.

Fig 12b




23/52




Close detected at
transmillter and receiver.
Connection broken.

Fig 12c



Cls detected at port receiver
 from node 12.
 Cls sourced from port
 transmitter.



Port 2 still connected.

Fig 13b





Fig 14a



27/52



Port 1 connected as
destination port.
Cls sourced from Port 1
transmitter.


Port 2 connected as source Port.
Open sourced from Port 2 receiver.

Fig 14b



28/52


Router detects Lip RX'd signal.
Router deasserts switched mode signal.



Lip F8 sourced by node 13.
Lip F8 replaced by Lip F7 at port receiver.
Lip F7 sourced at port transmitter.

Fig 15a


Router detects deassertion of port active.
Router takes port out of operational loop.



Lip F7 received at port transmitter.
Port deasserts port active signal.

Fig 15b

Router detects Lip RX'd signal since port
 active is now asserted.
 Router puts port back into the
 operational loop.




Node 13 "heals", source Lip F7.
 Lip F7 received at port receiver.
 Port asserts Port_Active.

Fig 15c



31/52

Router continues with loop
initialization



Port detects Lip F7 at port transmitter.
Port stops sourcing Lip F7 at port receiver.
Port stops sourcing Lip F7 at port transmitter.

Fig 15d




Fig. 16a




Fig. 16b




Fig. 16c



35/52




Fig. 17



36/52





Fig. 18



37/52

Fig. 19






Fig. 21




Fig. 20




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26





Fig. 27



DISK = Fibre Channel
Hard Disk Drive

Fig. 28





Fig. 29




47/52



DISK = Fibre Channel
Hard Disk Drive

Fig. 30



DISK = Fibre Channel
Hard Disk Drive

Fig. 31




Fig. 32



50/52




Fig. 33




Fig. 34




Fig. 35